

As an educator, you want to ensure the same engagement for students at home as if they are at school. It's vital to connect with remote students not only by sharing the teaching material, but also by delivering a clear view of the teacher and the environment. What students can see in the classroom have to be seen the same remotely, to let them feel more engaged in the class.

Innex's distance learning solutions offer a full range of webcam covering your needs. Simply mount the webcam on the tripod, connect to your laptop, and you are all set to start your online class, hassle-free. Having instant interactions, you and your students can together enjoy an immersive online learning experience no different from that in real classroom!



- 4K autofocus webcam
- 80° wide view angle
- Built-in omnidirectional microphones to capture every word with clarity



- 4K auto framing webcam
- 120° super wide view angle
- Embedded intelligent framing to focus on the teacher
- Built-in omnidirectional microphones



## innex C830

- 4K panoramic webcam
- Pioneering 180° view angle for full-room coverage
- Intelligent Al-driven facial tracking system to follow teacher's movement
- Flexible view angle switch
- Built-in omnidirectional microphones

## **Specifications**







## Camera

Max. Video Resolution	4K@30fps	4K@30fps	4K@30fps
Video Format	YUY2/MJPG/H.264	YUY2/MJPG/H.264	YUY2/MJPG/H.264
Focus	Auto Focus	Fixed Focus	Fixed Focus
Al Auto-Framing	No	Yes, camera embedded	Yes, multiple people simultaneous tracking by software
Field of View	Diagonal: 79.8° Horizontal: 67.8° Vertical:53.1°	Diagonal: 118.6° Horizontal: 108° Vertical:70°	Diagonal: 180° Horizontal: 170° Vertical:90° (5 Preset View Angle Switch)
Video Features	2D/3D DNR (Digital Noise Deduction) *3D DNR works better for dynamic frames; 2D DNR works better for static parts.	2D/3D DNR, Digital Zoom 5X, EPTZ (Software)	3D DNR, EPTZ (Software)
Microphone			
Built-in Microphone	Dual Stereo Omnidirectional Microphone Array	Dual Stereo Omnidirectional Microphone Array	Dual Omnidirectional Microphone Array
Microphone Features	Automatic Gain Control Noise Reduction	Automatic Gain Control Noise Reduction	Automatic Gain Control Noise Reduction
Pickup Range	13 ft / 4 m	13 ft / 4 m	13 ft / 4 m
Other			
Connectivity	USB Type C to Type A 2.0	USB Type C to Type A 2.0	USB Type C to Type A 3.0
Protocol	UVC; UAC; Plug-and-Play	UVC; UAC; Plug-and-Play	UVC; UAC; Plug-and-Play
Powered By	USB2.0 or above	USB2.0 or above	USB2.0 or above
Operating System	Window 10, 8, 7 . MacOS 10.12 or above Android 6.0 or above . Chrome OS	Window 10, 8, 7 . MacOS 10.12 or above Android 6.0 or above . Chrome OS	Window 10, 8, 7 . MacOS 10.12 or above Android 6.0 or above . Chrome OS
Mount Type	Clip / Tripod (1/4") / 360° Horizontal Rotation Swivel Mount	Clip / Tripod (1/4") / 360° Horizontal Rotation Swivel Mount	Clip / Tripod (1/4")
Cable	USB 2.0 Type C to Type A 4.9 ft / 1.5 m	USB 2.0 Type C to Type A 4.9 ft /1.5 m	USB 3.0 Type C to Type A 4.9 ft / 1.5 m
Operation Temperature Storage Temperature	0°C to 40°C / 32°F to 104°F -15°C to 55°C / -5°F to 131°F	0°C to 40°C / 32°F to 104°F -15°C to 55°C / -5°F to 131°F	0°C to 40°C / 32°F to 104°F -15°C to 55°C / -5°F to 131°F
Operating Humidity Storage Humidity	20% to 80% 20% to 90%	20% to 80% 20% to 90%	20% to 80% 20% to 90%
Product Dimensions	4.5x2.1x1.9" / 116x54.3x48 mm	4.6x2x2.2"/ 117.9x51x55.7 mm	5.6x1x2.8" / 144x26x73 mm
Net Weight	5.4oz / 155g	7.15 oz / 202.5 g	7.37 oz / 209.1 g
Accessories	USB Cable, Privacy Shutter	USB Cable	USB Cable, Wall Mount
	CE, FCC, EAC, RCM, WEEE	CE, FCC, EAC, RCM, WEEE	CE, FCC, EAC, RCM, WEEE

Г



Fun Technology Innovation Inc. funtechinnovation.com

info@funtechinnovation.com

We bring fun and passion to your everyday life!

© 2021 FunTech Innovation. All rights reserved.

innexrt1100501