

# nnex CD Series

Redefining Digital Signage with Precision & Performance

# Vivid, Secure, and Versatile!











**Brightness** 



Nonstop Productivity



178° Wide Viewing Angle



Software



Multi Size



Slim Bezel

# **Unmatched for Any Space!**

Captures attention in high-traffic areas with dynamic signage for promotions and information.



Corporate Offices & Meeting Rooms



**Educational Institutions** 



Retail & Public Spaces



Contact















## **Brilliance in Every Pixel!**

The Innex CD Series delivers stunning 4K resolution, a 178° wide viewing angle, and versatile display options in sizes from 43" to 86". Perfect for meeting rooms, classrooms, and retail spaces, it offers 24/7 durability and both landscape and portrait modes. With cloud control, managing content and displays is simple, allowing seamless updates and synchronization from anywhere for enhanced efficiency.



#### **Excellent Visual Performance**



### **4K Quality**

The CD Series offers exceptional 4K quality, ensuring that every image is presented with stunning clarity and precision. With 60Hz refresh rate and a 178° viewing angle, the display provides the best visual quality and readability for all types of content.



#### Portrait & Landscape Flexibility

The CD Series offers versatile portrait and landscape flexibility, easily switching between orientations to fit any content or environment.



## **Durability for High-Demand Use**

Designed for 24/7 operation, the CD Series is built to handle continuous, high-demand environments. Its durability ensures reliable performance around the clock, ideal for businesses needing dependable digital displays.



#### **Available in Multiple Sizes**

The CD Series is designed to offer flexibility and versatility across a range of environments by providing multiple size options: 43", 55", 65", 75", and 86" displays.

# **Easy & Secure Content Delivery**



The Digital Signage Software makes content management easy and secure. With user-friendly configuration options, you can quickly set up a secure cloud server for sharing and controlling digital signage content. Authorized users can access displays remotely, ensuring that content updates are efficient and safe, no matter where you are.



# nnexCD Series specs

(In U.S. Customary Units)

Model		CD43	CD55	CD65	CD75	CD86
	Display Dimension	43"	55"	65"	75"	86"
Display	Brightness		1	500cd/m² (TYP)	I	
	Contrast	1200: 1 (IPS)/ 4000:1 (VA)				
	Dynamic Contrast	5000:1				
	Anti-Glare	25% Haze				
	Back-Light	DLED				
	Resolution	3840x2160 (pixels, RGB)				
	Aspect Ratio	16:9				
	Response Time	8ms 8ms 6.5ms 8.5ms 8ms				
	Viewing Angle		l	178°		
	Display Color	1.07B (10bit)				
	Panel Frequency	60 Hz				
	Life Time	30,000 Hrs (min.)				
I/O Ports	Eno mino	DC xl				
		RJ45 x1				
	Input	USB OTG x1				
		USB 3.0 xl				
		HDMI x1				
		HDMI XI  TF card xI				
	Quitnut	Line xl				
	Output	IEEE 802.11a/b/g/n/ac Dual Band 2.4/5GHz				
	USB type Wi-Fi module					
	Ethernet Network	10M/100M/1000M 100V~240V AC				
Power	Power Input		1	1		
	Rated Power Consumption	Maximum ≤ 150W   Maximum ≤ 180W   Maximum ≤ 220W   Maximum ≤ 280W   Maximum ≤ 380W				
	Standby Power Consumption	≤ 0.5W				
	Speaker Output	10W x2				
Operating & Storage Environment	Operating Temperature	14 °F ~ 131 °F				
	Storage Temperature	32 °F ~ 113 °F				
	Operation Humidity	20% ~ 80%RH				
	Storage Temperature	20% ~ 90%RH				
Computing	Operating System	Android 11				
	RAM	DDR4 2GB				
	Internal Storage	EMMC 32GB				
	CPU/GPU	Cortex-A55*4				
	UI Resolution	4K				
Physical Spec	Panel Dimension	37.80 × 21.65 × 2.56"	48.43 × 27.56 × 2.56"	57.09 × 32.48 × 2.56"	65.75 × 37.40 × 2.76"	75.59 × 42.91 × 2.5
	Package Dimension	42.91 × 26.97 × 6.30"	53.54 × 33.07 × 6.30"	60.71 × 36.61 × 6.50"	72.05 × 45.08 × 7.68"	81.89 × 51.02 × 7.6
	Net Weight	9.8kg	33.51 lbs	48.50 lbs	62.83 lbs	82.67 lbs
	Packed Weight	21.49 lbs	42.33 lbs	59.52 lbs	85.98 lbs	109.13 lbs
	VESA Mount Point	15.75 × 15.75"	15.75 × 15.75"	15.75 × 15.75"	23.62 × 15.75"	31.50 × 23.62"
Compliance & Certification	Regulatory Certification	CE				
,	Accessories		ble x1, 4.84ft EU Pow ırranty Card, Safety			