

innex EU Plus Series

Google EDLA Certified Interactive Display



The Premium Upgrade. Your Google Ecosystem, Built Right In.

Upgrade your meeting room or classroom with a display that works exactly the way you do. The Innex EU Plus is a Google EDLA certified interactive display with everything you need built right in.

Powered by the advanced Android 15, and an 8-core processor, it delivers fast, reliable performance. Tailor the display to your exact workflow by downloading your favorite apps from the Google Play Store, or simply bring your own device (BYOD) to connect, share, and collaborate without the hassle.



Seamless Integration with Google Tools



Official Access to the Google Play Store

Google Certified



Seamlessly integrated with the Google ecosystem. Download your favorite apps directly from the Google Play Store for a familiar and secure experience.

4K AI Camera & 8-Mic Array



A stunning 48MP camera featuring three AI tracking modes and EPTZ framing control. Paired with an echo-canceling 8-mic array and powerful speakers with a subwoofer, every meeting looks and sounds crystal clear.

Responsive Touch



Experience ultra-smooth IR touch technology. With up to 40 points of touch and an included dual-tip stylus, writing feels just as natural as pen on paper.

Windows Ink Compatible



Fully compatible with Windows Ink. Easily annotate, sketch, and save your notes directly over your documents and presentations.

Wireless Sharing



Built-in Connect Pro wireless casting makes sharing effortless. Cast multiple devices at once and display up to 9 screens simultaneously to maximize teamwork.

Camera Streaming



Wirelessly access the display's camera right from your own laptop using Connect Pro. It delivers a true Bring Your Own Meeting (BYOM) experience with no cable clutter.



Funtech innovation

Contact

 funtechinnovation.com

 info@funtechinnovation.com

Follow us



innex EU Plus Series **SPECS**

Model	EU Plus 65	EU Plus 75	EU Plus 86	
Display	Display Dimension	65"	75"	86"
	Active Area	1428 × 804 mm / 49.1 x 31.2 in	1650 × 928 mm / 65 x 36.5 in	1895 × 1066 mm / 74.6 x 42 in
	Brightness	450 Typical		
	NTSC	72%		
	Dynamic Contrast	5000:1		
	Glass Hardness	8 H		
	Glass Thickness	3.2 mm / 0.12 in		
	Bonding Type	Zero bonding		
	Back-Light	D-Lit LED		
	Resolution	Ultra HD 3840 x 2160		
	Aspect Ratio	16:9		
	Response Time	8 ms Typical		
	Viewing Angle	178°		
	Display Color	1.07 B		
	Panel Frequency	60 Hz		
Other Features	Eco-Light Sensor, Flicker Free, Low Blue Light			
Touch / Interactive	Touch Technology	Infrared Touch		
	Touch Points	20 Points in Android / 40 Points in Windows		
	Accuracy (over 90% area)	± 1 mm / ± 0.04 in		
	Minimum Object Size	2 mm / 0.1 in		
	Touch Resolution	32768×32768		
	Touch Surface	Anti-Glare Glass		
	Touch Tool	Stylus, Finger, Eraser		
	Pen Type	Passive pen		
	Pen Tip Diameter	3 mm / 0.12 in ; 8mm / 0.31 in		
	Palm Rejection	YES		
	Touch Response Time	≤ 3.33 ms		
Single Point Scan Time	≥ 300 Hz			
Speaker, Camera and Microphone	Speaker Output	Built-in Speaker 20 W x 2, Subwoofer 20 W x1		
	Built-in Camera	48MP with FOV 120°		
	Microphone	8-Mic Array with Auto Gain Control / ANR/ AEC		
	Camera Function	Support Remote Control; Support Auto-Framing, Gallery, Speaker Tracking, Manual Mode		
Embedded Operating System	Operating System	Android 15.0 EDLA Certified		
	Chip	RK3588		
	RAM	16 GB		
	ROM	256 GB		
	CPU	A76x4 + A55x4		
	GPU	Mali - G610 MC4		
	NPU	Up to 6TOPs		
Power	Power Supply	100V - 240V AC		
	Consumption	Maximum ≤ 250 W	Maximum ≤ 350 W	Maximum ≤ 450 W
	Standby Mode	Yes		

innex EU Plus Series SPECS

Model		EU Plus 65	EU Plus 75	EU Plus 86
I/O Ports	Front	USB-B 3.0 x1 (for touch)		
		USB-A 3.0 x2 (Public)		
		USB-C x1 (DP Alt 1.2 4k@60 Hz in, USB 2.0, PD 20 V / 3.25 A)		
	Rear	HDMI in x1 (HDMI 2.0b)		
		HDMI in x3 (HDMI 2.0b)		
		HDMI out x1		
		DP in x1		
		USB-A 2.0 x1 (Public)		
		USB-A 3.0 x2 (Public x1, Android x1)		
		USB-C x1 (DP Alt 1.2 4k@60 Hz in, USB 2.0, PD 20V / 3.25A)		
		USB-C out x1 (DP out, USB 3.0 host, PD 5V / 1A)		
		USB-B 3.0 x3 (for touch)		
		Earphone out x1		
		Optical out x1		
		RS232 x1		
		RJ45 in / out x2 (1000M)		
		VGA x1		
		PC Audio in x1		
		MIC in x1		
		OPS Slot x1		
SD Slot x1				
AC in x1				
Bottom		USB Port x1 (for Wi-Fi USB Dongle)		
Operating & Storage Environment	Operating Temperature	0 °C - 45 °C / 32 °F - 113 °F		
	Storage Temperature	-20 °C - 60 °C / -4 °F - 140 °F		
	Operating Humidity	10% - 90%		
	Storage Humidity	10% - 90%		
Physical Spec	Product Dimension	1505 x 930 x 170 mm	1725 x 1055 x 170 mm	1970 x 1192 x 170 mm
		59.3 x 36.6 x 6.7 in	67.9 x 41.5 x 6.7 in	77.6 x 47x 6.7 in
	Package Dimension	1580 x 220 x 1000 mm	1790 x 220 x 1165 mm	2045 x 220 x 1280 mm
		62.2 x 8.7 x 39.4 in	70.5 x 8.7 x 45.9 in	80.5 x 8.7 x 50.4 in
	Net Weight	40 kg / 88.2 lbs	52.5 kg / 115.7 lbs	67 kg / 147.7 lbs
	Gross Weight	48 kg / 105.8 lbs	62.5 kg / 137.8 lbs	74.5 kg / 164.2 lbs
VESA Mount Point	500 x 400 mm / 19.7 x 15.7 in	600 x 400 mm / 23.6 x 15.7 in	800 x 400 mm / 31.5 x 15.7 in	
Sensor	NFC	YES		
	Motion Detection	N/A		
Compliance & Certification	Regulatory Certification	CE, FCC (all sizes); BSMI (65" & 86" only)		
Accessories Bag		3 m / 9.8 ft HDMI cable x1, 3 m / 9.8 ft USB B-A cable x1, 3 m / 9.8 ft Power cable (US / EU / UK / BR x1 each) Wall anchor x8, Self-tapping screw x8, Wall mount (pre-installed on back of display)		
Accessories Box		Remote control x1, High-precision dual-tip stylus x2, NFC card x3, Wi-Fi USB dongle, Quick start guide, Warranty card, Safety document		

Wi-Fi Dongle	Interface	USB Type
	Wi-Fi Spec	IEEE802.11b / g / n / ac / ax 2.4 GHz: 2400 - 2483.5 Hz ISM band 5 GHz: 5.15 - 5.25 GHz; 5.25 - 5.35 GHz; 5.47 - 5.725 GHz; 5.725 - 5.850 GHz